

PRODUCT CODE: 1401-E

**Product Name: Product Uses:** 

## LIVINGSTONE INTERNATIONAL PTY

100% PROUDLY AUSTRALIAN OWNED • SINCE 1984

Head Office: 106 - 116 Epsom Road, Phone: 1300 780 078 International Phone: +61 2 9313 6111

Rosebery NSW 2018 AUSTRALIA Fax: (02) 9313 6444

International Fax: +61 2 9313 6444

Email: sales@livingstone.com.au Website: www.livingstone.com.au

ABN: 66 052 001 144



PERSONAL **PROTECTION** 

### SAFETY DATA SHEET

**PAGE 1 OF 5** 

ISSUE DATE: 20/06/2017

**PRODUCT IDENTIFICATION** 

**REAGENT BOTTLE** 

Laboratory Glassware

**HAZARD IDENTIFICATION** 

Not classified as hazardous according to NOHSC/ASCC Criteria Not classified as dangerous goods by the criteria of the ADG Code

This material when properly handled according to good working and hygienic practices is not dangerous

to human health and the environment at ambient temperature.

Edges or broken pieces could be sharp and require careful handling, especially when glass thickness is

greater than 2mm.

#### **General Precautionary Measures**

**Emergency Overview** 

**Skin Contact:** 

| Code | <b>General Precautionary Statements</b>                                  | Hazard Class   | <b>Hazard Category</b> | Conditions for Use |
|------|--|----------------|------------------------|--------------------|
| P101 | If medical advice is needed,<br>have product container or label at hand. | As appropriate | N/A                    | Consumer products  |
| P102 | Keep out of reach of children.   | As appropriate | N/A                    | Consumer products  |
| P103 | Read label before use.   | As appropriate | N/A                    | Consumer products  |

This product in the natural state does not present an inhalation, ingestion or contact hazard. However, operations such as burning, welding, sawing, brazing, machining and grinding may irritate respiratory Inhalation:

system.

Eye contact with the sharp tip may cause puncture and bleeding which can possibly cause inflammation **Eye Contact:** 

and/or blindness. Molten form or dust particles may irritate or damage the eyes.

Skin contact with the sharp tip may cause puncture and bleeding, possibly may lead to inflammation if the product is contaminated or uncleaned. Repeated or prolonged contact with dust coming from

the glass may cause skin irritation, dermatitis or allergic reactions in sensitized individual. Molten form

could cause burns and irritation to skin.

Ingestion of harmful amount of this product as distributed may cause nausea or vomiting and can Ingestion:

cause damage to digestive system.

### SECTION 3

#### **COMPOSITION/INFORMATION ON INGREDIENTS**

| Chemical Name   | Chemical Formula               | CAS No.    |
|-----------------|--------------------------------|------------|
| Silicon Dioxide | SiO <sub>2</sub>               | 7631-86-9  |
| Boron           | В                              | 7440-42-8  |
| Sodium Oxide    | Na <sub>2</sub> O              | 1313-59-3  |
| Aluminum Oxide  | $Al_2O_3$                      | 1344-28-1  |
| Iron Oxide      | Fe <sub>2</sub> O <sub>3</sub> | 1309-37-1  |
| Potassium Oxide | K <sub>2</sub> O               | 12136-45-7 |



100% PROUDLY AUSTRALIAN OWNED • SINCE 1984 ABN: 66 052 001 144



**Head Office:** 106 - 116 Epsom Road, **Phone:** 1300 780 078 **International Phone:** +61 2 9313 6111 Rosebery NSW 2018 AUSTRALIA Fax: (02) 9313 6444

International Fax: +61 2 9313 6444

Email: sales@livingstone.com.au Website: www.livingstone.com.au

## SAFETY DATA SHEET

PRODUCT CODE: 1401-E PAGE 2 OF 5 ISSUE DATE: 20/06/2017

SECTION 4

**FIRST AID MEASURES** 

For over-exposure to airborne fumes and particulate, remove exposed person to fresh air. If breathing

is difficult or has stopped, administer artificial respiration or oxygen as indicated. Seek medical

attention promptly. Metal fume fever that could be generated from iron oxide and aluminum oxide may

be treated by bed rest, and administering a pain and fever reducing medication.

Treat for foreign body in the eye. Flush with large amounts of clean water to remove particles. **Eye Contact:** 

Seek immediate medical attention.

Remove contaminated clothing, wash affected area thoroughly with mild soap and water or use cotton **Skin Contact:** 

with antiseptic to clean up puncture. Apply pressure to affected area to stop the bleeding. If irritation,

inflammation or other symptoms develop, seek medical attention.

Do not induce vomiting and seek immediate medical advice. Ingestion:

SECTION 5

**FIRE FIGHTING MEASURES** 

**Suitable Extinguishing** 

**Equipment:** 

Inhalation:

Use dry chemical, foam or carbon dioxide fire extinguisher. Must also use extinguishing media most

appropriate for the surrounding fire.

Fire and Explosion Hazard:

This product does not present fire or explosion hazards under normal conditions. But, molten metal may react violently with water. High concentrations of metallic fines in the air may present an explosion

hazard. Metal fire produces toxic fumes like carbon monoxide, iron oxide, and etc. when burning.

**Special Protective Equipment:** 

Fire fighters should wear a self contained breathing apparatus (SCBA) which meets appropriate standards operated in positive pressure mode, and full protective equipment, including full bunker

gear.

SECTION 6

**ACCIDENTAL RELEASE MEASURES** 

Disposed in an appropriately permitted waste landfill, or disposed by other methods in accordance with local, state, and federal regulations. Finely divided, dry particles should be removed by vacuuming or wet sweeping to prevent spreading dusts. Avoid using compressed air.

> Not applicable to products in solid state. For spills involving finely divided particles, clean-up personnel should be protected against contact with eyes and skin. If material is in a dry state, avoid inhalation of

dust.

**Spill / Leak Procedures:** Fine, dry material should be removed by vacuuming or wet sweeping methods to prevent spreading

of dust. Avoid using compressed air. Do not release into sewers or waterways. Collect material in appropriate, labelled containers for recovery or disposal in accordance with federal, state, and local

regulations.

Follow applicable OSHA regulations (29 CFR 1910.120) and all other pertinent state and federal **Regulatory Requirements:** 

requirements.

Disposal: Follow applicable Federal, state, and local regulations.

SECTION 7

HANDLING AND STORAGE

Handle with care and in accordance with directions for use to prevent breakage. Do not eat, drink and **Safe Handling:** smoke in working area. Wash hand before and after handling. Remove contaminated clothing and

protective equipment before entering eating areas.

Store in a cool and dry place. Keep out of reach of children. Keep protected from sunlight, acids, fire/ **Storage Conditions:** 

heat sources, electrical wirings/sources and other incompatible materials.



100% PROUDLY AUSTRALIAN OWNED • SINCE 1984 ABN: 66 052 001 144



Head Office: 106 - 116 Epsom Road, Phone: 1300 780 078 International Phone: +61 2 9313 6111 Rosebery NSW 2018 AUSTRALIA Fax: (02) 9313 6444

International Fax: +61 2 9313 6444

Email: sales@livingstone.com.au Website: www.livingstone.com.au

SAFETY DATA SHEET

PRODUCT CODE: 1401-E PAGE 3 OF 5 ISSUE DATE: 20/06/2017

SECTION 8

#### **EXPOSURE CONTROL/PERSONAL INFORMATION**

#### **Exposure Standards:**

| Chemical Name | Limit at work (AGW)<br>TRGS 900 Regulation           | OSHA PEL¹  | ACGIH TLV <sup>2</sup>            |
|---------------|--|--|-----------------------------------|
| Iron          | 10mg/m³ – Breathable dust<br>3 mg/m³ – Alveolar dust | 10 mg/m³ – Iron oxide fume                             | 5mg/m³ – Iron oxide dust and fume |
| Silicon       | 4 mg/m³ – Breathable dust                            | 15 mg/m³ – Total dust<br>5 mg/m³ – Respirable fraction | 10mg/m³                           |

<sup>1</sup> OSHA Permissible Exposure Limits (PELs) are 8-hour TWA (time-weighted average) concentrations unless otherwise noted. A (C) designation denotes a ceiling limit, which should not be exceeded during any part of the working exposure unless otherwise noted. A Short Term Exposure Limit (STEL) is defined as a 15-minute exposure, which should not be exceeded at any time during a workday.

#### **Engineering Controls:**

Use controls as appropriate to minimize exposure to fumes and dusts during handling operations. Use lifting and work devices, e.g., crane, hoist, etc., within rated capacities and in accordance with manufacturer's instructions when handling these products.

- (1) Avoid breathing dust and fume.
- (2) Evaluate potential employee exposure.
- (3) Minimize generation of airborne emissions.
- (4) Maintain surfaces free as practical of accumulated material.
- (5) Use protective clothing as specified by an industrial hygienist or safety professional where exposure levels may be excessive.
- (6) Do not smoke in work area.

**Respiratory Protection:** 

**Skin and Eye Protection:** 

- (7) Wash hands before eating, drinking or smoking and after handling.
- (8) Change contaminated clothing before leaving work premises.

Provide general or local exhaust ventilation systems to minimize airborne concentrations. Local exhaust **Ventilation:** 

ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it

at its source.

**Administrive Controls:** Do not use compressed air to clean-up spills.

Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations

(29 CFR 1910.134) and, if necessary, wear a NIOSH-approved respirator. Select respirator based on

its suitability to provide adequate worker protection for given working conditions, level of airborne

contamination, and presence of sufficient oxygen.

For operations which result in elevating the temperature of the product to or above its melting point or

result in the generation of airborne particulates, use protective clothing, gloves and safety glasses to

prevent skin and eye contact. Use safety glasses or goggles and protective gloves as required for

handling operations.

#### SECTION 9 PHYSICAL/CHEMICAL PROPERTIES

Solid, transparent and odorless **Appearance and Odour: Evaporation Rate:** Not applicable

pH: Not applicable Flammability: Non-flammable, non-combustible

**Melting / Freezing Point:** ~1260°C **Vapour Pressure:** Not applicable **Boiling Point:** Not applicable Vapour Density: Not applicable 820°C (107.65 dPas) **Softening Point: Relative Density:** 2.23 - 2.49**Transformation Temperature:** 525°C **Solubility in Water:** Insoluble

**Flash Point:** No data available **Auto Ignition:** No data available

<sup>&</sup>lt;sup>2</sup> Threshold Limit Values (TLV) established by the American Conference of Governmental Industrial Hygienists (ACGIH) are 8-hour TWA concentrations unless otherwise noted.



100% PROUDLY AUSTRALIAN OWNED • SINCE 1984 ABN: 66 052 001 144



**Head Office**: 106 - 116 Epsom Road, **Phone**: 1300 780 078 **International Phone**: +61 2 9313 6111 Rosebery NSW 2018 AUSTRALIA Fax: (02) 9313 6444

International Fax: +61 2 9313 6444

Email: sales@livingstone.com.au Website: www.livingstone.com.au

### SAFETY DATA SHEET

PRODUCT CODE: 1401-E PAGE 4 OF 5 ISSUE DATE: 20/06/2017

STABILITY AND REACTIVITY

Stability: This product is stable under normal storage and handling conditions.

**Polymerization:** Hazardous polymerization cannot occur.

**Chemical Incompatibilities:** Iron oxide dusts in contact with calcium hypochlorite evolve oxygen and may cause an explosion.

Conditions to Avoid: Direct flame, ignition sources, incompatible materials.

SECTION 11 TOXICOLOGICAL INFORMATION

**Potential Health Effects** 

**Primary Entry Route -**

Inhalation:

This product in the natural state does not present an inhalation, ingestion or contact hazard. However,

operations such as burning, welding, sawing, brazing, machining and grinding may result in the

following effects if exposures exceed recommended limits as listed in Section 8.

**Target Organs:** Respiratory system

Presented below are the potential health effects that have been identified for the ingredients listed that Chronic Effects:

are of industrial hygiene significance.

Chronic inhalation of excessive concentrations of iron oxide fumes or dusts may result in the

development of a benign lung conditions known as pneumoconiosis, called siderosis, which is 1. IRON OXIDE:

observable as an X-ray change. But, no physical impairment of lung function has been associated with

siderosis.

2. SILICON: Silicon dusts are a low health risk by inhalation and should be treated as a nuisance dust.

The International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), and Carcinogenicity:

OSHA do not list glass products as carcinogens.

#### **Medical Conditions Aggravated by Long-Term Exposure**

Individuals with chronic respiratory disorders (i.e., asthma, chronic bronchitis, emphysema, etc.) may be adversely affected by any fume or airborne particulate matter exposure.

Other: No LC50 or LD50 has been established for this product as a whole.

Iron LD50: 30 g/kg oral (rat). **Aluminium LD50:** No data available

**Boron LD50:** 2000 mg/kg oral (mouse). Silicon LD50: 3160 mg/kg oral (rat). Mutagenicity, Teratogenicity: No data available

**ECOLOGICAL INFORMATION** 

This product in their usual form does not pose an ecological hazard.

No data available for the product as a whole. However, individual components of the product have been

found to be toxic to the environment. Metal dusts may migrate into soil and groundwater and be

ingested by wildlife.

No data available. **Environmental Fate:** 

**Ecotoxicity:** 



100% PROUDLY AUSTRALIAN OWNED • SINCE 1984 ABN: 66 052 001 144



**Head Office**: 106 - 116 Epsom Road, **Phone**: 1300 780 078 **International Phone**: +61 2 9313 6111 Rosebery NSW 2018 AUSTRALIA Fax: (02) 9313 6444

International Fax: +61 2 9313 6444

Email: sales@livingstone.com.au Website: www.livingstone.com.au

### SAFETY DATA SHEET

PRODUCT CODE: 1401-E PAGE 5 OF 5 ISSUE DATE: 20/06/2017

**Environmental Degradation:** No data available

No data available for the product as a whole. However, individual components of the product have been Soil Absorption / Mobility:

found to be absorbed by plants from soil.

SECTION 13 **DISPOSAL CONSIDERATIONS** 

Recycling of this product is strongly encouraged and suggested. If recycling is not possible due to contamination, the product and its packaging must be disposed of in accordance with the local and national regulations.

SECTION 14 TRANSPORT INFORMATION

This product is not classified as dangerous good under transport regulations

UN No.: **DG Class:** N/A N/A **Packaging Group:** N/A **Hazchem Code:** N/A

> SECTION 15 **REGULARITY INFORMATION**

**OSHA Regulations:** 

Air Contaminant (29 CFR 1910.1000, Table Z-1, and Z-1-A):

The product as a whole is not listed. However, individual components of the product are listed.

SECTION 16 OTHER INFORMATION

No other information.

### **END OF SDS**