LIVINGSTONE INTERNATIONAL PTY LTD

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 18/10/2001 Last Revision Date: 28/03/2025 Superseded Date: 21/01/2021

Version Number: 06

Product Code: APRHD72X130

SAFETY DATA SHEET

PAGE 1 OF 3

SECTION 1

PRODUCT IDENTIFICATION

Trade Name Lotrène

Product Name Liv Disposable Ponchos

Chemical Name Polyethylene (polyethylene) homo_polymer

Chemical FamilyPolyolefinChemical Abstract9002-88-4

Service (CAS) Number

(SECTION 2)

HAZARD IDENTIFICATION

Components of this product are not hazardous under OSHA Hazard Communication (29 CFR 1910.1200)

(SECTION 3)

COMPOSITION/INFORMATION ON INGREDIENTS

Ethylene - This material is stabilized

(SECTION 4)

FIRST AID MEASURES

Eye Contact Flush eyes with water if irritation occurs

Skin Contact If contact with molten product occurs, treat as thermal burn

IngestionNot ordinarily requiredInhalationNot ordinarily required

(SECTION 5)

FIRE FIGHTING MEASURES

Extinguishing Media

Use water fog, dry chemical or CO2.

Special Protective Equipment

for Fire Fighters

Material will not burn unless preheated. Do not enter fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots) including a positive pressure NIOSH* approved self-contained breathing apparatus. Cool fire exposed containers with water. Unusual Fire and

Explosion Hazard: Treat as a solid that can be burn.

Avoid accumulation and dispersion of dust to reduce explosion potential.

(SECTION 6)

ACCIDENTAL RELEASE MEASURES

Methods for Cleaning Up

Shovel sweep or use industrial vacuum cleaner. Avoid generating dust clouds. Put into containers for reclaiming or disposal as permitted by applicable of this material, the user should determine if the release is reportable under applicable laws and regulations.

SECTION 7

HANDLING AND STORAGE

Treat as solid that can burn. Avoid breathing dusts and process fumes. Avoid accumulation and dispersion of dust to reduce explosion potential. Adequate ventilation and/or engineering controls must be employed in high temperature processing to prevent exposure to potentially fly toxic/irritating fumes. Equipment must be earthed to avoid static electric charge.

Information provided on this document is presented in good faith and believed to be correct based on the best data currently available, Livingstone International makes no representations or warranties, expressed or implied as to the completeness or accuracy of the information. In no event will Livingstone International be liable for any errors or omissions in the information provided herein. Information is supplied upon the condition that any persons or corporate receiving same will make independent determination as to its suitability for their own purposes prior to use, and in no event will Livingstone International be responsible for damages of any nature whatsoever resulting from the use of product or reliance upon information provided. Information is provided on an "as is" basis, no representation or warranties, either expressed or implied of fitness for a particular purpose or of any other nature are made herein with respect to information of the product.

LIVINGSTONE INTERNATIONAL PTY LTD

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au WEBSITE: www.livingstone.com.au **PHONE**: 1300 548 289 FAX: 1300 780 008



Issue Date: 18/10/2001 Last Revision Date: 28/03/2025 Superseded Date: 21/01/2021

Version Number: 06 SAFETY DATA SHEET

Product Code: APRHD72X130

PAGE 2 OF 3

Storage Store away from oxidizing materials, in a cool, dry place with adequate ventilation and

absence of direct sunlight.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection Not ordinarily required, (OSHA* has established transitional occupational exposure limits for the

product and/or components for this product. Refer to 29 CFR 1910. 1000 for these transitional limits

and requirements for meeting these limits.)

Protective Clothing

Additional Protective

Protective clothing Additional Protective

Measures Adequate ventilation and/ or engineering controls are required when product is heated in processing to

prevent exposure to potentially toxic, irritating fumes.

(SECTION 9)

PHYSICAL/CHEMICAL PROPERTIES

Boiling Point Not Applicable **Solubility in Water** Insoluble 100 - 115 °C **Melting Point Vapour Pressure** Not Applicable **Flash Point** Not Applicable **Relative Density** 0.917 - 0.925 Odour Negligible Odour

Percent Volatile by Volume Nil

Appearance Solid Translucent

Auto Ignition Granules

350°C (ASTMD1929) **Temperature**

Flammable **Flammability**

STABILITY AND REACTIVITY

Stability Stable

Hazardous Polymerization Will not occur

Materials to avoid Strong Oxidizing Agents **Conditions to avoid** Temperature above 250 °C

Hazardous Decomposition

Products

At processing

temperature, some degree of thermal degradation will occur, Although highly dependant, on temperature and environmental conditions, a variety of decomposition products may be present ranging from simple hydrocarbons (methan and propane) to toxic/irritating gases such as carbon monoxide & dioxide, aldehydes and other organic vapors.

Information provided on this document is presented in good faith and believed to be correct based on the best data currently available, Livingstone International makes no representations or warranties, expressed or implied as to the completeness or accuracy of the information. In no event will Livingstone International be liable for any errors or omissions in the information provided herein. Information is supplied upon the condition that any persons or corporate receiving same will make independent determination as to its suitability for their own purposes prior to use, and in no event will Livingstone International be responsible for damages of any nature whatsoever resulting from the use of product or reliance upon information provided. Information is provided on an "as is" basis, no representation or warranties, either expressed or implied of fitness for a particular purpose or of any other nature are made herein with respect to information of the product.

LIVINGSTONE INTERNATIONAL PTY LTD

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au WEBSITE: www.livingstone.com.au **PHONE**: 1300 548 289 FAX: 1300 780 008



Issue Date: 18/10/2001 Last Revision Date: 28/03/2025

Superseded Date: 21/01/2021 Version Number: 06

Product Code: APRHD72X130

SAFETY DATA SHEET

PAGE 3 OF 3

SECTION 11 TOXICOLOGICAL INFORMATION

The product is non-toxic by composition. However, it should be treated as nuisance particulates, avoiding breathing dust or any fumes that may be generated during its processing. A knowledge of available toxicology information and of the physical and chemical properties of this material suggests that over-exposure is unlikely to aggravate existing medical conditions.

(SECTION 12) ECOLOGICAL INFORMATION

The material is not biodegradable. It can be recycled using suitable technology. It doesn't contain additive compounds of lead. cadmium and chromium. Disposal must be done in accordance with existing regulations. Land filing and incineration can be considered in most cases.

SECTION 13 DISPOSAL CONSIDERATIONS

All waste material should be packaged, labeled, transported and disposed or reclaimed in conformance with good engineering practices. Reclaim when possible.

SECTION 14 TRANSPORT INFORMATION

Department of Transportation Classification; Not hazardous by DOT* Regulations

(SECTION 15)

REGULATORY INFORMATION

Occupational Exposure Limits: There are no established limits for this product; however polyethylene dust should be treated as nuisance particulate. OSHA* Permissible Exposure Limit (PEL) is 15 mg/m3 respirable dust. ACGIH* Threshold Limit Value (TLV) is 10 mg/m3 total dust.

*These are American organizations:

Occupational Safety and Health Administration **OSHA** American Conference of Governmental Indust **ACGIH** NIOSH National Institute of Occupational Safety and Health DOT Department of Transportation

SECTION 16 OTHER INFORMATION

Reason for Revisions

To Bring to date

END OF SDS

Information provided on this document is presented in good faith and believed to be correct based on the best data currently available, Livingstone International makes no representations or warranties, expressed or implied as to the completeness or accuracy of the information. In no event will Livingstone International be liable for any errors or omissions in the information provided herein. Information is supplied upon the condition that any persons or corporate receiving same will make independent determination as to its suitability for their own purposes prior to use, and in no event will Livingstone International be responsible for damages of any nature whatsoever resulting from the use of product or reliance upon information provided. Information is provided on an "as is" basis, no representation or warranties, either expressed or implied of fitness for a particular purpose or of any other nature are made herein with respect to information of the product.