LIVINGSTONE INTERNATIONAL PTY LTD

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riodan Street Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au WEBSITE: www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



 Issue Date:
 24/06/2010

 Last Revision Date:
 20/07/2023

 Superseded Date:
 17/04/2018

 Version Number:
 04

SAFETY DATA SHEET

Product Code: APRLD85X130L

PAGE 1 OF 3

(SECTION 1) PRODUCT IDENTIFICATION

Identification of the Substance

Trade Name: Lotrène

Product Name: Livingstone Disposable Apron

Chemical Name: Polyethylene (polyethylene) homo-polymer

(SECTION 2) HAZARD IDENTIFICATION

Components of this product are not hazardous under OSHA Hazard Communication (29 CFR 1910.1200)

(SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

Ethylene CAS No.: 74-85-1

This material is stabilized

Chemical Family: Polyolefin
Chemical Abstract Service (CAS) 9002-88-4
Number:

SECTION 4 FIRST AID MEASURES

Eye Contact Flushes eyes with water if irritation occurs

Skin Contact If contact with molten product occurs, treat as thermal burn

IngestionNot ordinarily requiredInhalationNot ordinarily required

SECTION 5 FIRE FIGHTING MEASURES

Extinguishing Media: Use water fog, dry chemical or CO2. Special Protective Equipment for Fire Fighters: Material will not burn unless preheated. Do not enter fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots) including a positive pressure NIOSH* approved self-contained breathing apparatus. Cool fire exposed containers with water. Unusual Fire and Explosion Hazard: Treat as a solid that can burn. Avoid accumulation and dispersion of dust to reduce explosion potential.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Method for Cleaning Up: Shovel or sweep or use industrial vacuum cleaner. Avoid generating dust clouds. Put into containers for reclaiming or disposal as permitted by applicable national, state and local regulations. In the event of an uncontrolled release of this material, the user should determine if the release is reportable under applicable laws and regulations.

Information provided on this document is presented in good faith and believed to be correct based on the best data currently available, Livingstone International makes no representations or warranties, expressed or implied as to the completeness or accuracy of the information. In no event will Livingstone International be liable for any errors or omissions in the information provided herein. Information is supplied upon the condition that any persons or corporate receiving same will make independent determination as to its suitability for their own purposes prior to use, and in no event will Livingstone International be responsible for damages of any nature whatsoever resulting from the use of product or reliance upon information provided. Information is provided on an "as is" basis, no representation or warranties, either expressed or implied of fitness for a particular purpose or of any other nature are made herein with respect to information of the product.

LIVINGSTONE INTERNATIONAL PTY LTD

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riodan Street Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE**: www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



 Issue Date:
 24/06/2010

 Last Revision Date:
 20/07/2023

 Superseded Date:
 17/04/2018

 Version Number:
 04

SAFETY DATA SHEET

Product Code: APRLD85X130L

PAGE 2 OF 3

SECTION 7

HANDLING AND STORAGE

7.1 Treat as solid that can burn.

Avoid breathing dusts and process fumes. Avoid accumulation and dispersion of dust to reduce explosion potential. Adequate ventilation and/or engineering controls must be employed in high temperature processing to prevent exposure to potentially fly toxic/irritating fumes. Equipment must be earthed to avoid staticelectric changed

7.2 Storage

Store away from oxidizing materials, in a cool, dry place with adequate ventilation and absence of direct sunlight.

SECTION 8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection: Not ordinarily required. (OSHA* has established transitional occupational exposure limits for the product and/or components for this product. Refer to 29 CFR 1910. 1000 for these transitional limits and requirements for meeting these limits).

Protective clothing Additional Protective Protective clothing Additional Protective

Measures

Adequate ventilation and/or engineering controls are required when product is heated in

processing to prevent exposure to potentially toxic, irritating fumes.

(SECTION 9)

PHYSICAL/CHEMICAL PROPERTIES

Boiling Point Not Applicable **Solubility in Water** Insoluble **Melting Point** 100-115°C **Vapor Pressure** Not Applicable **Flash Point** Not Applicable **Vapor Density** Not Applicable **Relative Density** 0.917 - 0.925 Odor Negligible Odor

Percent Volatile by Volume Nil

Appearance Solid Translucent Granules **Auto Ignition Temperature** 350 °C (ASTM D1929)

Flammability Flammable

Information provided on this document is presented in good faith and believed to be correct based on the best data currently available, Livingstone International makes no representations or warranties, expressed or implied as to the completeness or accuracy of the information. In no event will Livingstone International be liable for any errors or omissions in the information provided herein. Information is supplied upon the condition that any persons or corporate receiving same will make independent determination as to its suitability for their own purposes prior to use, and in no event will Livingstone International be responsible for damages of any nature whatsoever resulting from the use of product or reliance upon information provided. Information is provided on an "as is" basis, no representation or warranties, either expressed or implied of fitness for a particular purpose or of any other nature are made herein with respect to information of the product.

LIVINGSTONE INTERNATIONAL PTY LTD

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riodan Street Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au WEBSITE: www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



 Issue Date:
 24/06/2010

 Last Revision Date:
 20/07/2023

 Superseded Date:
 17/04/2018

 Version Number:
 04

SAFETY DATA SHEET

Product Code: APRLD85X130L

PAGE 3 OF 3

(SECTION 10) STABILITY AND REACTIVITY

Stability Stable

Hazardous Polymerization Will not occur

Materials to avoidStrong Oxidizing AgentsConditions to avoidTemperature above 250°C

Hazardous Decomposition Products At processing

temperature, some degree of thermal degradation will occur. Although highly dependant, on temperature and environmental conditions, a variety of decomposition products maybe present ranging from simple hydrocarbons (methan and propane) to toxic/irritating gases such as carbon monoxide & dioxide, aldehydes and other organic vapors

SECTION 11 TOXICOLOGICAL INFORMATION

The product is non-toxic by composition. However, it should be treated as nuisance particulates, avoiding breathing dust or any fumes that may be generated during its processing. A knowledge of available toxicology information and of the physical and chemical properties of this material suggests that over-exposure is unlikely to aggravate existing medical conditions.

SECTION 12 ECOLOGICAL INFORMATION

The material is not biodegradable. It can be recycled using suitable technology. It doesn't contain additive compunds of lead, cadmium and chromium. Disposal must be done in accordance with existing regulations. land filling and incineration can be considered in most cases.

SECTION 13 DISPOSAL CONSIDERATIONS

All waste material should be packaged, labeled, transported and disposed or reclaimed in conformance with applicable laws & regulations and in conformance with good engineering practices. Reclaim when possible.

(SECTION 14) TRANSPORT INFORMATION

Department of Transportation Classification; Not hazardous by DOT* Regulations.

SECTION 15 REGULATORY INFORMATION

Occupational Exposure Limits: There are no established limits for this product; however, polyethylene dust should be treated as nuisance particulate. OSHA* Permissible Exposure Limit (PEL) is 5 mg/m3 total dust, and 5 mg/m3 respirable dust. ACGIH* Threshold Limit Value (TLV) is 10 mg/m3 total dust.

*These are American organizations:

OSHA = Occupational Safety and Health Administration

ACGIH = American Conference of Governmental Industrial Hygienists

NIOSH = National Institute of Occupational Safety and Health

DOT = Department of Transportation

(SECTION 16) OTHER INFORMATION

Reason for Revision:To bring to date

END OF SDS

Information provided on this document is presented in good faith and believed to be correct based on the best data currently available, Livingstone International makes no representations or warranties, expressed or implied as to the completeness or accuracy of the information. In no event will Livingstone International be liable for any errors or omissions in the information provided herein. Information is supplied upon the condition that any persons or corporate receiving same will make independent determination as to its suitability for their own purposes prior to use, and in no event will Livingstone International be responsible for damages of any nature whatsoever resulting from the use of product or reliance upon information provided. Information is provided on an "as is" basis, no representation or warranties, either expressed or implied of fitness for a particular purpose or of any other nature are made herein with respect to information of the product.