Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 1 OF 24

SECTION 1 PRODUCT IDENTIFICATION

Product Identifier Product name GGold Cross Benzoin Compound Tincture Friar's Balsam Chemical Name Not Applicable ethanone, 2-hydroxy-1,2-diphenyl-, (benzoin) mixture with aloe, storax (styrax) and tolu balsam, tincture; Compound Benzoin Tincture; Co. Benz. Synonyms Tinc:; Tinct. Benz. Co.; BENZOIN COMPOUND TINCTURE 200ML; 101529: GOLD CROSS FRIARS BALSALM 200ML; 101466: GOLD CROSS

Relevant identified uses of the substance or mixture and uses advised against

FRIARS BALSAM 25ML

For the treatment of chronic bronchitis by inhalation and as a tincture for skin infections.

The chemicals in this group are salts of structurally related linear alkylbenzene sulfonates (LASs) that have surfactant properties Linear alkylbenzene sulfonates (LAS) are, by volume, the most important group of synthetic anionic surfactant today. LAS are mainly used in laundry detergents and cleaning agents. LAS are frequently used as the sodium salts as the sole surfactant in a formulation or in conjunction with other anionic, nonionic or cationic surfactants.

The chemicals in this group can have an alkyl chain between 10 and 16 carbon atoms. The main commercial grade material is typically limited to a range of 10-14 or 10-13 carbons with a dodecyl-component of 20-35 %. The carbon chain distribution of the chemicals will vary depending on the method of production and the source of the precursor chemicals.

The chemicals in this group are expected to have similar toxicity, which is primarily due to the alkylbenzene sulfonate anion. They share similar physico-chemical properties, including density and melting points.

The solubility of the homologues differs based on the alkyl chain length, usually decreasing with increasing chain length. However, as the chemicals are also mixtures of positional isomers, chemicals with the same alkyl chain distribution (same average carbon number) can have different properties depending on the 2-phenyl isomer content (consistent with 4-substitution as the major product with smaller amounts of the 2-substitution)

Relevant identified uses

LAS consist of an alkyl chain attached to a benzene ring in the para position to the sulfonate group. Sometimes toluene, xylene and naphthalene are used in place of benzene. The homologue distribution in commercial products covers alkyl chain lengths from C10 to C13 with an average chain length of C11.6. LAS raw materials are derived from linear alkyl benzenes in which the ring is attached to a C-atom which is itself attached to two other C-atoms. The benzene ring may be attached to any of the C atoms from C2 to C6 but not to C1. Structures in which the benzene ring may be attached to different C atoms are described as isomers. E.g., the structure with a C12 alkyl chain and the benzene ring attached at the second alkyl carbon is designated as the C12-2-isomer and abbreviated C12-2.

LAS can be represented structurally as:

H3C(CH3)xCH(C6H4S)3.Na+)CH2(CH2)yCH3 - x+y=9

Compared to traditional soaps branched alkyl benzenesulfonates (BAS) offer superior tolerance to hard water and better foaming. However, the highly branched tail made it difficult to biodegrade.

The term "linear" refers to the starting alkenes rather than the final product. The alkylation of linear alkenes, even 1- alkenes such as 1-dodecene gives several isomers of phenyldodecane.

Under ideal conditions the cleaning power of BAS and LAS is very similar, however LAS performs slightly better in normal use conditions, due to it being less affected by hard water. Within LAS itself the detergency of the various isomers are fairly similar, however their physical properties (Krafft point, foaming etc.) are noticeably different In particular the Krafft point of the high 2-phenyl product remains below 0 deg C up to 25% LAS whereas the low 2-phenyl cloud point is 5 deg C. This behavior is often exploited by producers to create either clear or cloudy products.

Emergency telephone number

Association / Organisation	Poisons Information Centre
Emergency telephone numbers	13 11 26
Other emergency telephone numbers	Not Available

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au WEBSITE: www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 2 OF 24

SECTION 2 HAZARD IDENTIFICATION

Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification ^[1]	Flammable Liquids Category 3, Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 1, Specific Target Organ Toxicity - Repeated Exposure Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)









Signal word

Danger

Hazard statement(s)

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P264	Wash all exposed external body areas thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.
P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au WEBSITE: www.livingstone.com.au PHONE: 1300 548 289 FAX: 1300 780 008



01/07/2025 Issue Date:

Last Revision Date: N/A Superseded Date: N/A **Version Number:**

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 3 OF 24

Precautionary statement(s) Storage

P403+P235

Store in a well-ventilated place. Keep cool.

Precautionary statement(s) Disposal

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

COMPOSITION/INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name		
9000-73-1	10	nenzoin resinoid absolute Sumatra		
Not Available		(balsamic acids calculated as cinnamic acid)		
8023-62-9	10	Styrax		
CAS No	%[weight]	Name		
8001-97-6	2	aloes		
64-17-5	70-76	ethanol		
Legend:	1. Classified by Chemwatch: 2. C	Classification drawn from HCIS: 3. Classification drawn from Regulation (FU) No. 1272/2008 - Annex VI: 4		

Classification drawn from C&L; * EU IOELVs available

(SECTION 4)

FIRST AID MEASURES

Description of first aid measures

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin Contact

Eye Contact

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- ▶ Seek medical attention in event of irritation

Inhalation

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor

Ingestion

- If swallowed do **NOT** induce vomiting
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 4 OF 24

Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to ethanol:

- Acute ingestion in non-tolerant patients usually responds to supportive care with special attention to prevention of aspiration, replacement of fluid and correction of nutritional deficiencies (magnesium, thiamine pyridoxine, Vitamins C and K).
- Give 50% dextrose (50-100 ml) IV to obtunded patients following blood draw for glucose determination.
- Comatose patients should be treated with initial attention to airway, breathing, circulation and drugs of immediate importance (glucose, thiamine).
- Decontamination is probably unnecessary more than 1 hour after a single observed ingestion. Cathartics and charcoal may be given but are probably not effective in single ingestions.
- Fructose administration is contra-indicated due to side effects.

SECTION 5

FIRE FIGHTING MEASURES

Extinguishing media

- Alcohol stable foam.
- ► Dry chemical powder
- ► BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only

Special hazards arising from the substrate or mixture

Fire Fighting

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
 - DO NOT approach containers suspected to be hot.
 - Cool fire exposed containers with water spray from a protected location.
 - If safe to do so, remove containers from path of fire.

Liquid and vapour are flammable.

- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.
- Vapour may travel a considerable distance to source of ignition.
- Heating may cause expansion or decomposition leading to violent rupture of containers.

▶ On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include: carbon monoxide (CO)

carbon dioxide (CO2)

other pyrolysis products typical of burning organic material.

HAZCHEM

Fire/Explosion Hazard

•2Y

(SECTION 6)

ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au WEBSITE: www.livingstone.com.au **PHONE**: 1300 548 289 FAX: 1300 780 008



01/07/2025 Issue Date:

Last Revision Date: N/A Superseded Date: **Version Number:**

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 5 OF 24

Methods and material for containment and cleaning up

	٠	Remove	all	ignition	sources.
--	---	--------	-----	----------	----------

Minor Spills

- Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment. Contain and absorb small quantities with vermiculite or other absorbent material.
- Collect residues in a flammable waste container

Chemical Class: alcohols and glycols

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
-----------------	------	-------------	------------	-------------

LAND SPILL - SMALL

cross-linked polymer - particulate	1	shovel	shovel	R, W, SS
cross-linked polymer - pillow	1	throw	pitchfork	R, DGC, RT
sorbent clay - particulate	2	shovel	shovel	R,I, P
wood fiber - pillow	3	throw	pitchfork	R, P, DGC, RT
treated wood fiber - pillow	3	throw	pitchfork	DGC, RT
foamed glass - pillow	4	throw	pichfork	R, P, DGC, RT

LAND SPILL - MEDIUM

cross-linked polymer - particulate	1	blower	skiploader	R,W, SS
polypropylene - particulate	2	blower	skiploader	W, SS, DGC
sorbent clay - particulate	2	blower	skiploader	R, I, W, P, DGC
polypropylene - mat	3	throw	skiploader	DGC, RT
expanded mineral - particulate	3	blower	skiploader	R, I, W, P, DGC
polyurethane - mat	4	throw	skiploader	DGC, RT

Major Spills

Legend

DGC: Not effective where ground cover is dense

R: Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

RT:Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control:

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au WEBSITE: www.livingstone.com.au PHONE: 1300 548 289 FAX: 1300 780 008



01/07/2025 Issue Date:

Last Revision Date: N/A Superseded Date: N/A **Version Number:**

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 6 OF 24

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling Containers, even those that have been emptied, may contain explosive vapours Do NOT cut, drill, grind, weld or perform similar operations on or near containers. DO NOT allow clothing wet with material to stay in contact with skin Avoid all personal contact, including inhalation. Safe handling Wear protective clothing when risk of overexposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid smoking, naked lights or ignition sources. Avoid generation of static electricity. DO NOT use plastic buckets. Earth all lines and equipment. Use spark-free tools when handling Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions. Store in original containers in approved flammable liquid storage area. Store away from incompatible materials in a cool, dry, well-ventilated area. DO NOT store in pits, depressions, basements or areas where vapours may be trapped No smoking, naked lights, heat or ignition sources. Storage areas should be clearly identified, well illuminated, clear of obstruction and accessible only to trained and authorised personnel adequate security must be provided so that unauthorised personnel do not have access. Store according to applicable regulations for flammable materials for storage tanks, containers, piping, buildings, rooms, cabinets, allowable quantities and minimum storage distances. Use non-sparking ventilation systems, approved explosion proof equipment and intrinsically safe electrical systems Other information Have appropriate extinguishing capability in storage area (e.g. portable fire extinguishers - dry chemical, foam or carbon dioxide) and flammable gas detectors. Keep adsorbents for leaks and spills readily available. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. In addition, for tank storages (where appropriate): Store in grounded, properly designed and approved vessels and away from incompatible materials. For bulk storages, consider use of floating roof or nitrogen blanketed vessels; where venting to atmosphere is possible, equip storage tank vents with flame arrestors; inspect tank vents during winter conditions for vapour/ ice build-up. ▶ Storage tanks should be above ground and diked to hold entire contents.

Conditions for safe storage, including any incompatibilities

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i): Drums and jerry cans must be of the non-removable head type. (ii): Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C) Suitable container
 - Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.
 - Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages
 - In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au WEBSITE: www.livingstone.com.au PHONE: 1300 548 289 FAX: 1300 780 008

TEEL-3



01/07/2025 Issue Date:

Last Revision Date: N/A Superseded Date: **Version Number:**

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 7 OF 24

TEEL-1

- are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents.
- reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen

Storage incompatibility

- react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium
- should not be heated above 49 deg. C. when in contact with aluminium equipment
- Balsams are both air and moisture sensitive.

(SECTION 8)

EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	ethanol	Ethyl alcohol	1000 ppm / 1880 mg/m3	Not Available	Not Available	Not Available

Emergency Limits

Ingredient

				· === ·
ethanol	Not Available	Not Available		15000* ppm
Ingredient	Original IDLH		Revised IDLH	
benzoin resinoid absolute Sumatra	Not Available		Not Available	
Styrax	Not Available		Not Available	
aloes	Not Available		Not Available	
ethanol	3,300 ppm		Not Available	

TFFL-2

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
benzoin resinoid absolute	Е	≤ 0.01 mg/m³
Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
Sumatra		
Styrax	E	≤ 0.1 ppm
aloes	E	≤ 0.01 mg/m³
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to range of exposure concentrations that are expected to protect worker health.	

MATERIAL DATA

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 8 OF 24

Air Speed:

For ethanol:

Odour Threshold Value: 49-716 ppm (detection), 101 ppm (recognition)

Eye and respiratory tract irritation do not appear to occur at exposure levels of less than 5000 ppm and the TLV-TWA is thought to provide an adequate margin of safety against such effects. Experiments in man show that inhalation of 1000 ppm caused slight symptoms of poisoning and 5000 ppm caused strong stupor and morbid sleepiness. Subjects exposed to 5000 ppm to 10000 ppm experienced smarting of the eyes and nose and coughing. Symptoms disappeared within minutes. Inhalation also causes local irritating effects to the eyes and upper respiratory tract, headaches, sensation of heat intraocular tension, stupor, fatigue and a need to sleep. At 15000 ppm there was continuous lachrymation and coughing.

Exposed individuals are NOT reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

ClassOSF Description

- A 550 Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV-TWA for example) is being reached, even when distracted by working activities
- B 26-550 As "A" for 50-90% of persons being distracted
- C 1-26 As "A" for less than 50% of persons being distracted
- D 0.18-1 10-50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached

Type of Contaminant:

E <0.18 As "D" for less than 10% of persons aware of being tested

Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Appropriate engineering controls

76	- 1
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 9 OF 24

with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

- · Adequate ventilation is typically taken to be that which limits the average concentration to no more than 25% of the LEL within the building room or enclosure containing the dangerous substance.
- · Ventilation for plant and machinery is normally considered adequate if it limits the average concentration of any dangerous substance that might potentially be present to no more than 25% of the LEL. However, an increase up to a maximum 50% LEL can be acceptable where additional safeguards are provided to prevent the formation of a hazardous explosive atmosphere. For example, gas detectors linked to emergency shutdown of the process might be used together with maintaining or increasing the exhaust ventilation on solvent evaporating ovens and gas turbine enclosures.
- Temporary exhaust ventilation systems may be provided for non-routine higher-risk activities, such as cleaning, repair or maintenance in tanks or other confined spaces or in an emergency after a release. The work procedures for such activities should be carefully considered. The atmosphere should be continuously monitored to ensure that ventilation is adequate and the area remains safe. Where workers will enter the space, the ventilation should ensure that the concentration of the dangerous substance does not exceed 10% of the LEL (irrespective of the provision of suitable breathing apparatus)

Individual protection measures, such as personal protective equipment













Eve and face protection

Safety glasses with side shields.

- Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

Skin protection

Hands/feet protection

See Hand protection below

- ► Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- · frequency and duration of contact,
- · chemical resistance of glove material,
- · glove thickness and
- · glove thic

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
 When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN
- 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.

· Contaminated gloves should be replaced.
As defined in ASTM F-739-96 in any application, gloves are rated as:

- · Excellent when breakthrough time > 480 min
- · Good when breakthrough time > 20 min
- · Fair when breakthrough time < 20 min
- · Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 10 OF 24

	It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Body protection	See Other protection below
Other protection	 Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Ensure there is ready access to a safety shower. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a
	conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

GOLD CROSS FRIARS BALSALM

Material	СРІ
BUTYL	Α
NEOPRENE	Α
NITRILE	Α
NITRILE+PVC	Α
PE/EVAL/PE	Α
PVC	В
NATURAL RUBBER	С
NATURAL+NEOPRENE	С

- * CPI Chemwatch Performance Index
- A: Best Selection
- B: Satisfactory; may degrade after 4 hours continuous immersion
- C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	Air-line*	A-2	A-PAPR-2 ^
up to 10 x ES	-	A-3	-
10+ x ES	-	Air-line**	-

- * Continuous Flow; ** Continuous-flow or positive pressure demand
- ^ Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 deqC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 11 OF 24

(SECTION 9) PHYSICAL/CHEMICAL PROPERTIES

Information on basic	physical and	chemical	properties
----------------------	--------------	----------	------------

Appearance	Colourless flammable liquid with balsamic odour; mixes with water.		
		5 1 11 11 11 11 11 11 11	
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	<61	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	19 ethanol	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	3.3 ethanol	Volatile Component (%vol)	100
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY		
Reactivity	See section 7	
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. 	
Possibility of hazardous reactions	See section 7	
Conditions to avoid	See section 7	
Incompatible materials	See section 7	
Hazardous decomposition products	See section 5	

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

Inhaled

Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

Inhalation hazard is increased at higher temperatures.

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 12 OF 24

	Inhalation hazard is increased at higher temperatures. Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination The most common signs of inhalation overexposure to ethanol, in animals, include ataxia, incoordination and drowsiness for those surviving narcosis. The narcotic dose for rats, after 2 hours of exposure, is 19260 ppm.	
Ingestion	urine red. Accidental ingestion of the	aloes on the gastro-intestinal tract may cause pelvic congestion and in large doses may cause nephritis. Colours alkaline me material may be damaging to the health of the individual. yl alcohol, "alcohol," may produce nausea, vomiting, bleeding from the digestive tract, abdominal pain, and diarrhoea. Effects Mild: impaired vision, co-ordination and reaction time; emotional instability Moderate: Slurred speech, confusion, inco-ordination, emotional instability, disturbances in perception and senses, possible blackouts, and impaired objective performance in standardized tests. Possible double vision, flushing, fast heart rate, sweating and incontinence. Slow breathing may occur rarely and fast breathing may develop in cases of metabolic acidosis, low blood sugar and low blood potassium. Central nervous system depression may progress to coma.
		Severe: cold clammy skin, low body temperature and low blood pressure. Atrial fibrillation and heart block have been reported. Depression of breathing may occur, respiratory failure may follow serious poisoning, choking on vomit may result in lung inflammation and swelling. Convulsions due to severe low blood sugar may also occur. Acute liver inflammation may develop. nes (HA), which occur in numerous medicinal plants, produce an irritant action on the gastrointestinal tract. Intestinal cosides to very reactive anthrones which increase the net secretion of fluid into the lumen by irritation of the intestinal
	wall. This process produ	ces a laxative action. The presence of two hydroxy groups in the 1,8-position is essential for this laxative effect.
Skin Contact	The material produces moderate skin irritation; evidence exists, or practical experience predicts, that the material either produces moderate inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant, but moderate, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. Skin contact is not though to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man. Balsams and resins derived from plants may cause skin sensitisation; since many are chemically related by their content of esters (often cinnamic and benzoic acid derivatives), multiple sensitivities may occur. Many of the ingredients in balsams also occur in spices and essential oils and cross-sensitivity has been reported.	

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 13 OF 24

Eye

When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation. Direct contact of the eye with ethanol may cause immediate stinging and burning with reflex closure of the lid and tearing, transient injury of the corneal epithelium and hyperaemia of the conjunctiva. Foreign-body type discomfort may persist for up to 2 days but healing is usually spontaneous and complete.

Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals.

Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance who are likely to become hyper-responsive.

Substances than can cuase occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing air-way hyper-responsiveness. The latter substances are not classified as asthmagens or respiratory sensitisers. Wherever it is reasonably practicable, exposure to substances that can cuase occupational asthma should be prevented. Where this is not possible the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there

should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance.

On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.

Chronic

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Long-term exposure to ethanol may result in progressive liver damage with fibrosis or may exacerbate liver injury caused by other agents. Repeated ingestion of ethanol by pregnant women may adversely affect the central nervous system of the developing foetus, producing effects collectively described as foetal alcohol syndrome. These include mental and physical retardation, learning disturbances, motor and language deficiency, behavioural disorders and reduced head size.

Consumption of ethanol (in alcoholic beverages) may be linked to the development of Type I hypersensitivities in a small number of individuals. Symptoms, which may appear immediately after consumption, include conjunctivitis, angioedema, dyspnoea, and urticarial rashes. The causative agent may be acetic acid, a metabolite (1).

(1) Boehncke W.H., & H.Gall, Clinical & Experimental Allergy, 26, 1089-1091, 1996

Chronic use of hydroxyanthraquinone (HA) laxatives reduces laxative potency resulting in an increased intake to produce a useful effect. This in turn produces damage to the intestinal cell wall and myenteric nerve plexi (resulting in the inhibition of myenteric activity) and sometimes severe loss of water, sodium as well as an increase in aldosterone secretion rates which increases loss of potassium. Some HAs are genotoxic in a variety of in vitro short-term assays. All HA with hydroxygroups in the 1,8-position (i.e laxative actives) act as tumour promoters in primary liver cell cultures (inducing mitosis) and in C3H-mouse fibroblasts (after treatment with a low dose inducer). Carcinogenic action in rodents was demonstrated after feeding rats and mice with danthron and 1-hydroxyanthraquinone. There is limited evidence that long-term abuse of HA laxatives is correlated to colon cancer. The action of the HA is most probably related to oxidative stress.

GOLD CROSS FRIARS	TOXICITY	IRRITATION
BALSALM	Not Available	Not Available
benzoin resinoid absolute	TOXICITY	IRRITATION
Sumatra	Oral (Rat) LD50: >5000 mg/kg ^[1]	Not Available
	TOXICITY	IRRITATION
Styrax	Oral (Rat) LD50: >=2140 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50: >2000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
_	TOXICITY	IRRITATION
aloes	Oral (Rat) LD50: >5000 mg/kg ^[2]	Not Available
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 17100 mg/kg ^[1]	Eye (rabbit): 500 mg SEVERE
	Inhalation(Rat) LC50: 64000 ppm4h ^[2]	Eye (rabbit):100mg/24hr-moderate
ethanol	Oral (Rat) LD50: 7060 mg/kg ^[2]	Eye: adverse effect observed (irritating) ^[1]

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au WEBSITE: www.livingstone.com.au PHONE: 1300 548 289 FAX: 1300 780 008



01/07/2025 Issue Date:

Last Revision Date: N/A Superseded Date: N/A Version Number:

SAFETY DATA SHEET

ct Code: BEN5370	04	PAGE
		Skin (rabbit):20 mg/24hr-moderate
		Skin (rabbit):400 mg (open)-mild
		Skin: no adverse effect observed (not irritating) ^[1]
Legend:	Value obtained from Europe ECHA Registered Substance specified data extracted from RTECS - Register of Toxic Effe	s - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise ect of chemical Substances
GOLD CROSS FRIARS BALSALM	The material may produce severe irritation to the eye causing produce conjunctivitis.	g pronounced inflammation. Repeated or prolonged exposure to irritants may
BENZOIN RESINOID ABSOLUTE SUMATRA	The aryl alkyl alcohol (AAA) fragrance ingredients are a diverse group of chemical structures with similar metabolic and toxicity profiles. The AAA fragrances demonstrate low acute and subchronic dermal and oral toxicity. At concentrations likely to be encountered by consumers, AAA fragrance ingredients are non-irritating to the skin. The potential for eye irritation is minimal. With the exception of benzyl alcohol and to a lesser extent phenethyl and 2-phenoxyethyl AAA alcohols, human sensitization studies, diagnipatch tests and human induction studies, indicate that AAA fragrance ingredients generally have no or low sensitization potential. Available indicate that the potential for photosensitization is low. NOAELs for maternal and developmental toxicity are far in excess of current human exposure levels. No carcinogenicity in rats or mice was observed in 2-year chronic testing of benzyl alcohol or a-methylbenzyl alcohol; the latter did induce species and gender-specific renal adenomas in male rats at the high dose. There was no to little genotoxicity, mutagenicity, or clastogenicity the mutagenicity in vitro bacterial assays, and in vitro mammalian cell assays. All in vivo micronucleus assays were negative. It is concluded that these materials would not present a safety concern at current levels of use as fragrance ingredients The Research Institute for Fragrance Materials (RIFM) Expert Panel For certain benzyl derivatives:	
	functional group (aldehyde or ester) that is hydrolysed and/or derivatives are efficiently excreted primarily in the urine. The similarity of their toxicologic properties is a reflection their par In general, members of this group are rapidly absorbed throu urine either unchanged or as conjugates of benzoic acid deri which case, free benzoic acid is excreted unchanged. Absorp this group and structural relatives. These substances exhibit benzoate, and 2-hydroxybenzoate (salicylate) esters which cacids. The benzyl alcohol and benzaldehyde derivatives are excreted unchanged or as glycine or glucuronic acid conjuga additional minor metabolic options become available. O-dem glucuronic acid or sulfate conjugates. At high dose levels, gu	enzoate (salicylate) esters) contain a benzene ring bonded directly to an oxygenat roxidised to a benzoic acid derivative. As a stable animal metabolite, benzoic acid se reaction pathways have been reported in both aquatic and terrestrial species. Tritipation in these common metabolic pathways. Igh the gastrointestinal tract, metabolised primarily in the liver, and excreted in the vatives At high doses, conjugation pathways (e.g., glycine) may be saturated; in otion, distribution and excretion studies have been conducted several members of remarkably similar patterns of pharmacokinetics and metabolism. The benzyl, omprise this category are hydrolysed to the corresponding alcohols and carboxylic oxidised to the corresponding benzoic acid derivatives that are subsequently ites. If methoxy or phenolic functional groups are present on the benzene ring, ethylation yields the corresponding phenol that is subsequently excreted as the t microflora may act to produce minor amounts of reduction metabolites. r than 5,000 mg/kg bw demonstrating the low to moderate toxicity of these

Repeat dose toxicity: Overall, numerous repeat-dose studies using various routes of exposure have been conducted in different animal species with members of this chemical category or their close structural relatives. It is important to note that all the benzyl derivatives in this category are eventually metabolised to a common metabolite, benzoic acid, and are rapidly excreted in the urine as benzoic acid or as its glycine, sulfate, or glucuronic acid conjugate. For this reason, the repeat-dose studies currently available provide adequate support for the safety of the benzyl derivatives. Moreover, the levels at which no adverse effects were reported were sufficiently high to accommodate any potential differences among the members of the category.

Reproductive toxicity: Several reproductive toxicity studies have been conducted with representatives of this group and produced no evidence of reproductive toxicity As with the repeat-dose studies, the benzyl derivatives generally follow the similar metabolic pathways and the studies conducted provide an adequate database for this endpoint. In addition, the dose levels tested provide margins of safety large enough to accommodate any differences among the group.

Developmental toxicity: Representative substances from this group were tested for developmental toxicity with uniform results, and indicated no teratogenic potential in the absence of maternal toxicity. Again, the representative substances undergo similar metabolism to the entire benzyl derivative group and therefore, provide an adequate representation for this endpoint.

Genetic toxicity: Overall, in vitro and in vivo genotoxicity studies have been conducted with substances representing the structural characteristics of the benzyl category. The results of these studies were predominantly negative demonstrating a low order of genotoxic potential.. Limited positive and/or equivocal findings have been reported for 3 aldehydes and benzyl acetate, but, in most cases, other studies of the same endpoint with same test substance show no activity. Most importantly, in vivo studies on benzaldehyde derivatives and closely related benzyl esters have all yielded negative results. These negative in vivo genotoxicity assays are supported by the lack of tumorigenicity in chronic animal studies with representatives of this group.

Data available for more than 100 in vitro genotoxicity assays for 9 members of the category and five metabolic precursors or metabolites of benzyl derivatives indicate a low genotoxic potential for members of this chemical category Equivocal results have been reported mainly for aromatic aldehydes in the MLA and ABS assays.

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 15 OF 24

A member or analogue of a group of benzyl derivatives generally regarded as safe (GRAS) based in part on their self-limiting properties as flavouring substances in food; their rapid absorption. metabolic detoxification, and excretion in humans and other animals, their low level of flavour use, the wide margin of safety between the conservative estimates of intake and the no-observed-adverse effect levels determined from chronic and subchronic studies and the lack of significant genotoxic and mutagenic potential. This evidence of safety is supported by the fact that the intake of benzyl derivatives as natural components of traditional foods is greater than the intake as intentionally added flavouring substances. All members of this group are aromatic primary alcohols, aldehydes, carboxylic acids or their corresponding esters or acetals. The substances in this group:

- · contain a benzene ring substituted with a reactive primary oxygenated functional group or can be hydrolysed to such a functional group
- the major pathway of metabolic detoxification involves hydrolysis and oxidation to yield the corresponding benzoic acid derivate which is excreted either as the free acid or the glycine conjugate
- they show a consistent pattern of toxicity in both short- and long- term studies and
- they exhibit no evidence of genotoxicity in standardised batteries of in vitro and in vivo assays.

The benzyl derivatives are rapidly absorbed through the gut, metabolised primarily in the liver, and excreted in the urine as glycine conjugates of benzoic acid derivatives.

In general, aromatic esters are hydrolysed in vivo through the catalytic activity of carboxylesterases, the most important of which are the A-esterases. Hydrolysis of benzyl and benzoate esters to yield corresponding alcohols and carboxylic acids and hydrolysis of acetals to yield benzaldehyde and simple alcohols have been reported in several experiments.

The alcohols and aldehydes are rapidly oxidised to benzoic acid while benzoate esters are hydrolysed to benzoic acid

Flavor and Extract Manufacturers Association (FEMA)

For benzyl alkyl alcohols:

Unlike benzylic alcohols, the beta-hydroxyl group of the members of this cluster is unlikely to undergo phase II metabolic activation. Instead, the beta-hydroxyl group is expected to contribute to detoxification via oxidation to hydrophilic acid. Despite structural similarity to carcinogenic ethyl benzene, only a marginal concern has been assigned to phenethyl alcohol due to limited mechanistic analogy. For herozoates:

Acute toxicity: Benzyl alcohol, benzoic acid and its sodium and potassium salt can be considered as a single category regarding human health, as they are all rapidly metabolised and excreted via a common pathway within 24 hrs. Systemic toxic effects of similar nature (e.g. liver, kidney) were observed. However with benzoic acid and its salts toxic effects are seen at higher doses than with benzyl alcohol.

The compounds exhibit low acute toxicity as for the oral and dermal route. The LD50 values are > 2000 mg/kg bw except for benzyl alcohol which needs to be considered as harmful by the oral route in view of an oral LD50 of 1610 mg/kg bw. The 4 hrs inhalation exposure of benzyl alcohol or benzoic acid at 4 and 12 mg/l as aerosol/dust respectively gave no mortality, showing low acute toxicity by inhalation for these compounds.

Benzoic acid and benzyl alcohol are slightly irritating to the skin, while sodium benzoate was not skin irritating. No data are available for potassium benzoate but it is also expected not to be skin irritating. Benzoic acid and benzyl alcohol are irritating to the eye and sodium benzoate was only slightly irritating to the eye. No data are available for potassium benzoate but it is expected also to be only slightly irritating to the eye.

Sensitisation: The available studies for benzoic acid gave no indication for a sensitising effect in animals, however occasionally very low positive reactions were recorded with humans (dermatological patients) in patch tests. The same occurs for sodium benzoate. It has been suggested that the very low positive reactions are non-immunologic contact urticaria. Benzyl alcohol gave positive and negative results in animals. Benzyl alcohol also demonstrated a maximum incidence of sensitization of only 1% in human patch testing. Over several decades no sensitization with these compounds has been seen among workers.

Repeat dose toxicity: For benzoic acid repeated dose oral toxicity studies give a NOAEL of 800 mg/kg/day. For the salts values > 1000 mg/kg/day are obtained. At higher doses increased mortality, reduced weight gain, liver and kidney effects were observed.

For benzyl alcohol the long-term studies indicate a NOAEL > 400 mg/kg bw/d for rats and > 200 mg/kg bw/d for mice. At higher doses effects on bodyweights, lesions in the brains, thymus, skeletal muscle and kidney were observed. It should be taken into account that administration in these studies was by gavage route, at which saturation of metabolic pathways is likely to occur.

Mutagenicity: All chemicals showed no mutagenic activity in *in vitro* Ames tests. Various results were obtained with other *in vitro* genotoxicity assays. Sodium benzoate and benzyl alcohol showed no genotoxicity *in vivo*. While some mixed and/or equivocal *in vitro* chromosomal/chromatid responses have been observed, no genotoxicity was observed in the *in vivo* cytogenetic, micronucleus, or other assays. The weight of the evidence of the *in vitro* and *in vivo* genotoxicity data indicates that these chemicals are not mutagenic or clastogenic. They also are not carcinogenic in long-term carcinogenicity studies.

In a 4-generation study with benzoic acid no effects on reproduction were seen (NOAEL: 750 mg/kg). No compound related effects on reproductive organs (gross and histopathology examination) could be found in the (sub) chronic studies in rats and mice with benzyl acetate, benzyl alcohol, benzaldehyde, sodium benzoate and supports a non-reprotoxic potential of these compounds. In addition, data from reprotoxicity studies on benzyl acetate (NOAEL >2000 mg/kg bw/d; rats and mice) and benzaldehyde (tested only up to 5 mg/kg bw; rats) support the non-reprotoxicity of benzyl alcohol and benzoic acid and its salts.

Developmental toxicity: In rats for sodium benzoate dosed via food during the entire gestation developmental effects occurred only in the presence of marked maternal toxicity (reduced food intake and decreased body weight) (NOAEL = 1400 mg/kg bw). For hamster (NOEL: 300 mg/kg bw), rabbit (NOEL: 250 mg/kg bw) and mice (CD-1 mice, NOEL: 175 mg/kg bw) no higher doses (all by gavage) were tested and no maternal toxicity was observed. For benzyl alcohol: NOAEL= 550 mg/kg bw (gavage; CD-1 mice). LOAEL = 750 mg/kg bw (gavage mice). In this study maternal toxicity was observed e.g. increased mortality, reduced body weight and clinical toxicology. Benzyl acetate: NOEL = 500 mg/kg bw (gavage rats). No maternal toxicity was observed.

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 16 OF 24

Cross-reactivity is also expected between ester derivatives and their parent alcohols, as the esters will be hydrolysed by esterases in the skin. Esters of important contact allergens that can be activated by hydrolysis in the skin are isoeugenol acetate, eugenyl acetate and geranyl acetate all of which are known to be used as fragrance ingredients.

Linear alkylbenzene sulfonates (LAS) are classified as Irritant (Xi) with the risk phrases R38 (Irritating to skin) and R41 (Risk of serious damage to eyes) according to CESIO (CESIO 2000). LAS are not included in Annex 1 of list of dangerous substances of Council Directive 67/548/EEC. Linear alkylbenzene sulfonic acids (LABS) are strong acids (pKa<2) are classified as corrosive (R34) Branched materials exhibit comparable toxicity to linear species.

Acute toxicity: The available data indicate minimal to moderate toxicity, with LD50 values ranging from 500 to 2000 mg/kg body weight (bw). Acute inhalation data also indicate a lack of significant toxicity. Available dermal exposure data also shows a lack of significant toxicity. LAS are readily absorbed by the gastrointestinal tract after oral administration in animals. LAS are not readily absorbed through the skin. The bulk is metabolised in the liver to sulfophenylic carboxyl acids. The metabolites are excreted primarily via the urine and faeces. The main urinary metabolites in rats are sulfophenyl butanoic acid and sulfophenyl pentanoic acid. Accumulation of LAS or its main metabolites has not been established in any organ after repeated oral ingestion.

No serious injuries or fatalities in man have been reported following accidental ingestion of LAS-containing detergent. The main clinical signs observed after oral administration to rats of doses near or greater than the LD50 values consisted of reduced voluntary activity, diarrhoea, weakness etc. Death usually occurred within 24 hours of administration. Rats appear to be more sensitive to LAS than mice.

LAS and branched alkylbenzene sulfonates may cause irritation of the eyes, skin and mucous membranes. LAS are relatively more irritating to the skin than the corresponding branched alkylbenzene sulfonates. The potential of LAS to irritate the skin depends on the concentration applied. LAS have been classified as irritating to skin at concentrations above 20% according to EU-criteria. Human skin can tolerate contact with solution of up to 1% LAS for 24 hours resulting in only mild irritation. Application of > 5% LAS to the eyes of rabbits produced irritation. Concentration of < 0.1% LAS produced mild to no irritation.

Skin sensitization was not seen in 2,294 volunteers exposed to LAS or in 17,887 exposed to formulations of LAS.

Repeat dose toxicity: A feeding study indicated that LAS, when administered for 2 years at extremely high levels (0.5%) in the diets to rats, produced no adverse effects on growth, health or feed efficiency.

Genotoxicity: The mutagenic potential of LAS was tested using *Salmonella typhimurium* strains, using Ames test. In these studies, LAS was not mutagenic. The available long-term studies are inadequate for evaluating the carcinogenic potential of LAS in laboratory animals. The studies available (oral administration to rats and mice) do not show any evidence of carcinogenicity.

Reproductive toxicity: In general no specific effect of LAS on reproductive processes has been seen, although dosages causing maternal toxicity may also induce some effects on reproduction. No teratogenic effects attributed to LAS exposure have been observed. Environmental and Health Assessment of Substances in Household Detergents and Cosmetic Detergent Products, Environment Project, 615, 2001. Torben Madsen et al: Miljoministeriet (Danish Environmental Protection Agency)

For aromatic sulfonic acids

Aromatic sulfonic acids are very corrosive as was demonstrated in skin and eye irritation studies, in the acute oral studies, and in the single repeated dose oral study.

Health records from industrial manufacturing exposure, including manufacturing plant book of injuries and a physician report, show toluene-4-sulphonic acid (as handled in manufacturing plants; i.e., a 65% aqueous solution with < 5% free sulphuric acid) is an irritant to the eye and skin.

STYRAX

There is a single, key study for sensitization of the aromatic sulphonic acids. None of the tested animals showed positive responses in a, well documented, GLP guinea pig sensitization study with toluene-4-sulphonic acid (CAS No. 104-15-4). The test substance can be considered a non-sensitizer in guinea pigs as none of the test animals showed a positive response to combined intradermal and topical induction followed by topical challenge.

Repeat dose toxicity:

A GLP guideline study with p-toluenesulphonic acid (CAS No. 104-15-4) reported no adverse effects to male and female rats exposed orally for 28 days. The highest dose was 500 mg/kg bw/day (>490 mg/kg bw/day based on >98% active ingredient). Therefore the NOAEL was set at 500 mg/kg bw/day.

Toxicity to reproduction:

No fertility studies are reported for the aromatic sulphonic acids. There are however studies for the chemically related hydrotrope substances that looked at reproductive organs and development of offspring. Hydrotropes are the salt form of the sulphonic acids and therefore are used as read-across for this endpoint. The 90-day oral rat and oral mouse studies and the 2-year chronic dermal rat and mouse studies with the closely related compound sodium xylene sulfonate (CAS No. 1300-72-7) included examination of sex organs of both sexes. No treatment related effects on reproductive organs were reported at doses roughly equivalent to those in the developmental toxicity study. he NOAEL for both maternal and foetal toxicity was the highest dose tested - 3000 mg/kg bw /day which is equivalent to 936 mg active ingredient per kilogram body weight per day. The conclusion of the study was no indications of developmental toxicity including teratogenesis.

Genetic toxicity:

There is a fully documented, GLP Guideline (OECD 471) Ames Test and a fully documented, GLP Guideline (OECD 473) Chromosome Aberration Test for one of the aromatic sulphonic acids, p-toluenesulphonic acid (CAS No. 104-15-4). Both tests were conducted with and without metabolic activation. The Ames test exposed up to 5000 micrograms/plate and the chromosome aberration test exposed up to 1902 micrograms per liter of the test substance. These studies conclude the substance is neither mutagenic norcytotoxic.

There is an additional, published report of an Ames Test for another of the aromatic sulphonic acids, benzenesulfonic acid (CAS No. 98-11-3). Exposures up to 10,000 micrograms/plate were done with and without metabolic activation. The conclusion is the same as for the p-toluenesulphonic acid; that is, not mutagenic and not cytotoxic.

There are no in vivo mutagenicity studies for the aromatic sulphonic acids, but there are two in vivo mouse micronucleus studies for the related hydrotropes – sodium cumene sulfonate (CAS 28348-53-0) and calcium xylene sulfonate (CAS 28088-63-3). Both are GLP-compliant Guideline mouse micronucleus studies with full documentation. Both studies conclude the test substances were not mutagenic in these assays. Disulfonic acids have not been the subject of concern.

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 17 OF 24

	Carcinogenicity: There are no carcinogenicity studies for the aromatic sulphonic acids Two hydrotrope studies involve 2-year rat and mouse dermal exposures conducted under GLP. Up to 240 mg (rats) and 727 mg (mice) sodium xylenesulfonate/kg body weight in 50% ethanol were dosed 5 days per week for 104 weeks. There were no treatment related incidences of mononuclear cell leukenia, neoplasms, or nonneoplatic lesions of the skin and other organs. The increased incidence of epidermal hyperplasia may have been related to exposure to the test substance. The NOAEL was reported as 240 mg/kg bw/day for rats and 727 mg/kg bw/day for mice. Elimination: The US EPA has evaluated the metabolism of analogs in in the sodium alkyl naphthalenesulfonate cluster (SANS), a group of sodium salts of naphthalenesulfonic acids. In a US EPA final rule for SANS, it was stated that "the 1- or 2-sulfonic acid sodium salt moieties on the naphthalene ring may provide a handle by which these compounds can be readily conjugated and eliminated."
ALOES	NOTE: Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA.
GOLD CROSS FRIARS BALSALM & BENZOIN RESINOID ABSOLUTE SUMATRA & STYRAX	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. No significant acute toxicological data identified in literature search.
GOLD CROSS FRIARS BALSALM & BENZOIN RESINOID ABSOLUTE SUMATRA & ETHANOL	The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.
BENZOIN RESINOID ABSOLUTE SUMATRA & ALOES	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.
	Adverse reactions to fragrances in perfumes and in fragranced cosmetic products include allergic contact dermatitis, photosensitivity, immediate contact reactions (contact urticaria), and pigmented contact dermatitis. Airborne and connubial contact dermatitis occur. Intolerance to perfumes, by inhalation, may occur if the perfume contains a sensitising principal. Symptoms may vary from general illness, coughing, phlegm, wheezing, chest-tightness, headache, exertional dyspnoea, acute respiratory illness, haytever, and other respiratory diseases (including asthma). Perfumes can induce hyper-reactivity of the respiratory tract without producing an IgE-mediated allergy or demonstrable respiratory obstruction. This was shown by placebo-controlled challenges of nine patients to "perfume mix". The same patients were also subject to perfume provocation, with or without a carbon filter mask, to ascertain whether breathing through a filter with active carbon would prevent symptoms. The patients breathed through the mouth, during the provocations, as a nose clamp was used to prevent nasal inhalation. The patient's earlier symptoms were verified; breathing through the carbon filter had no protective effect. The symptoms were not transmitted via the olifactory nerve but they may have been induced by trigeminal reflex via the respiratory tract or bit eyes. Cases of occupational asthma induced by perfume substances such as isoamyl acetate, limonene, cinnamaldehyde and benzaldehyde, tend to give persistent symptoms even though the exposure is below occupational exposure limits. Inhalation intolerance has also been produced in animals. The emissions of five fragrance products, for one hour, produced various combinations of sensory irritation, pulmonary irritation, decreases in expiratory airflow velocity as well as alterations of the functional observational battery indicative of neurotoxicity in mice. Neurotoxicity was found to be more severe after mice were repeatedly exposed to the fragrance products, being four brands of

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 18 OF 24

BENZOIN RESINOID ABSOLUTE SUMATRA & STYRAX

both in terms of primary prevention (avoiding sensitisation) and secondary prevention (avoiding relapses of allergic contact dermatitis in those already sensitised), is an important objective of public health risk management measure.

Hands: Contact sensitisation may be the primary cause of hand eczema, or may be a complication of irritant or atopic hand eczema. The number of positive patch tests has been reported to correlate with the duration of hand eczema, indicating that long-standing hand eczema may often be complicated by sensitisation. Fragrance allergy may be a relevant problem in patients with hand eczema; perfumes are present in consumer products to which their hands are exposed. A significant relationship between hand eczema and fragrance contact allergy has been found in some studies based on patients investigated for contact allergy. However, hand eczema is a multi-factorial disease and the clinical significance of fragrance contact allergy in (severe) chronic hand eczema may not be clear.

Axillae Bilateral axillary (underarm) dermatitis may be caused by perfume in deodorants and, if the reaction is severe, it may spread down the arms and to other areas of the body. In individuals who consulted a dermatologist, a history of such first-time symptoms was significantly related to the later diagnosis of perfume allergy.

Face Facial eczema is an important manifestation of fragrance allergy from the use of cosmetic products (16). In men, after-shave products can cause an eczematous eruption of the beard area and the adjacent part of the neck and men using wet shaving as opposed to dry have been shown to have an increased risk of of being fragrance allergic.

Irritant reactions (including contact urticaria): Irritant effects of some individual fragrance ingredients, e.g. citral are known. Irritant contact dermatitis from perfumes is believed to be common, but there are no existing investigations to substantiate this, Many more people complain about intolerance or rashes to perfumes/perfumed products than are shown to be allergic by testing. This may be due to irritant effects or inadequate diagnostic procedures. Fragrances may cause a dose-related contact urticaria of the non-immunological type (irritant contact urticaria). Cinnamal, cinnamic alcohol, and Myroxylon pereirae are well recognised causes of contact urticaria, but others, including menthol, vanillin and benzaldehyde have also been reported. The reactions to Myroxylon pereirae may be due to cinnamates. A relationship to delayed contact hypersensitivity was suggested, but no significant difference was found between a fragrance-allergic group and a control group in the frequency of immediate reactions to fragrance ingredients in keeping with a nonimmunological basis for the reactions seen.

Pigmentary anomalies: The term "pigmented cosmetic dermatitis" was introduced in 1973 for what had previously been known as melanosis faciei feminae when the mechanism (type IV allergy) and causative allergens were clarified. It refers to increased pigmentation, usually on the face/neck, often following sub-clinical contact dermatitis. Many cosmetic ingredients were patch tested at non-irritant concentrations and statistical evaluation showed that a number of fragrance ingredients were associated: jasmine absolute, ylang-ylang oil, cananga oil, benzyl salicylate, hydroxycitronellal, sandalwood oil, geraniol, geranium oil.

Photo-reactions Musk ambrette produced a considerable number of allergic photocontact reactions (in which UV-light is required) in the 1970s and was later banned from use in the EU. Nowadays, photoallergic contact dermatitis is uncommon. Furocoumarins (psoralens) in some plant-derived fragrance ingredients caused phototoxic reactions with erythema followed by hyperpigmentation resulting in Berloque dermatitis. There are now limits for the amount of furocoumarins in fragrance products. Phototoxic reactions still occur but are rare.

General/respiratory: Fragrances are volatile and therefore, in addition to skin exposure, a perfume also exposes the eyes and naso-respiratory tract. It is estimated that 2-4% of the adult population is affected by respiratory or eye symptoms by such an exposure. It is known that exposure

to fragrances may exacerbate pre-existing asthma. Asthma-like symptoms can be provoked by sensory mechanisms. In an epidemiological investigation, a significant association was found between respiratory complaints related to fragrances and contact allergy to fragrance ingredients, in addition to hand eczema, which were independent risk factors in a multivariate analysis.

Fragrance allergens act as haptens, i.e. low molecular weight chemicals that are immunogenic only when attached to a carrier protein. However, not all sensitising fragrance chemicals are directly reactive, but require previous activation. A prehapten is a chemical that itself is non- or low-sensitising, but that is transformed into a hapten outside the skin by simple chemical transformation (air oxidation, photoactivation) and without the requirement of specific enzymatic systems. A prohapten is a chemical that itself is non- or low-sensitising but that is transformed into a hapten in the skin (bioactivation) usually via enzyme catalysis. It is not always possible to know whether a particular allergen that is not directly reactive acts as a prehapten or as a prohapten, or both, because air oxidation and bioactivation can often give the same product (geraniol is an example). Some chemicals might act by all three pathways.

Prohaptens

Compounds that are bioactivated in the skin and thereby form haptens are referred to as prohaptens.

In the case of prohaptens, the possibility to become activated is inherent to the molecule and activation cannot be avoided by extrinsic measures. Activation processes increase the risk for cross-reactivity between fragrance substances. Crossreactivity has been shown for certain alcohols and their corresponding aldehydes, i.e. between geraniol and geranial (citral) and between cinnamyl alcohol and cinnamal.

The human skin expresses enzyme systems that are able to metabolise xenobiotics, modifying their chemical structure to increase hydrophilicity and allow elimination from the body. Xenobiotic metabolism can be divided into two phases: phase I and phase II. Phase I transformations are known as activation or functionalisation reactions, which normally introduce or unmask hydrophilic functional groups. If the metabolites are sufficiently polar at this point they will be eliminated. However, many phase I products have to undergo subsequent phase II transformations, i.e. conjugation to make them sufficiently water soluble to be eliminated. Although the purpose of xenobiotic metabolism is detoxification, it can also convert relatively harmless compounds into reactive species. Cutaneous enzymes that catalyse phase I transformations include the cytochrome P450 mixed-function oxidase system, alcohol and aldehyde dehydrogenases, monoamine oxidases, flavin-containing monooxygenases and hydrolytic enzymes. Acyltransferases, glutathione S-transferases, UDP-glucuronosyltransferases and sulfotransferases are examples of phase II enzymes that have been shown to be present in human skin. These enzymes are known to catalyse both activating and deactivating biotransformations, but the influence of the reactions on the allergenic activity of skin sensitisers has not been studied in detail. Skin sensitising prohaptens can be recognised and grouped into chemical classes based on knowledge of xenobiotic bioactivation reactions, clinical observations and/or in vivo and in vitro studies of sensitisation potential and chemical reactivity.

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 19 OF 24

QSAR prediction: The relationships between molecular structure and reactivity that form the basis for structural alerts are based on well established principles of mechanistic organic chemistry. Examples of structural alerts are aliphatic aldehydes (alerting to the possibility of sensitisation via a Schiff base reaction with protein amino groups), and alpha,beta-unsaturated carbonyl groups, C=C-CO- (alerting to the possibility of sensitisation via Michael addition of protein thiol groups). Prediction of the sensitisation potential of compounds that can act via abiotic or metabolic activation (pre- or prohaptens) is more complex compared to that of compounds that act as direct haptens without any activation. The autoxidation patterns can differ due to differences in the stability of the intermediates formed, e.g. it has been shown that autoxidation of the structural isomers linalool and geraniol results in different major haptens/allergens. Moreover, the complexity of the prediction increases further for those compounds that can act both as pre- and prohaptens. In such cases, the impact on the sensitisation potency depends on the degree of abiotic activation (e.g. autoxidation) in relation to the metabolic activation

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	₩	Reproductivity	×
Serious Eye Damage/Irritation	₩	STOT - Single Exposure	×
Respiratory or Skin sensitisation	¥	STOT - Repeated Exposure	~
Mutagenicity	×	Aspiration Hazard	×

Legend:

🔀 - Data either not available or does not fill the criteria for classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

GOLD CROSS FRIARS BALSALM	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Availabl
	Endpoint	Test Duration (hr)	Species	Value	Source
benzoin resinoid absolute Sumatra	Not Available	Not Available	Not Available	Not Available	Not Availabl
	Endpoint	Test Duration (hr)	Species	Value	Sourc
<u>.</u> .	EC50	72h	Algae or other aquatic plants	>0.13mg/l	2
Styrax	EC50	48h	Crustacea	>7.8mg/l	2
	NOEC(ECx)	72h	Algae or other aquatic plants	<0.022mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
aloes	Not Available	Not Available	Not Available	Not Available	Not Availab
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	275mg/l	2
.01	EC50	48h	Crustacea	2mg/l	4
ethanol	EC50	96h	Algae or other aquatic plants	<0.001mg/L	4
	LC50	96h	Fish	42mg/l	4
	EC50(ECx)	96h	Algae or other aquatic plants	<0.001mg/L	4
Legend:			CHA Registered Substances - Ecotoxicological Information Aquatic Hazard Assessment Data 6. NITE (Japan) - Bio		

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au WEBSITE: www.livingstone.com.au **PHONE**: 1300 548 289 FAX: 1300 780 008



01/07/2025 Issue Date:

Last Revision Date: N/A Superseded Date: N/A **Version Number:**

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 20 OF 24

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For Ethanol:

log Kow: -0.31 to -0.32; Koc 1: Estimated BCF= 3; Half-life (hr) air: 144: Half-life (hr) H2O surface water: 144:

Henry's atm m3 /mol: 6.29E-06: BOD 5 if unstated: 0.93-1.67.63%

COD: 1.99-2.11,97%; ThOD: 2.1.

Environmental Fate: Terrestrial - Ethanol quickly biodegrades in soil but may leach into ground water; most is lost by evaporation. Ethanol is expected to have very high mobility in soil. Volatilization of ethanol from moist soil surfaces is expected to be an important fate process. The potential for volatilization of ethanol from dry soil surfaces may exist. Biodegradation is expected to be an important fate process for ethanol based on half-lives on the order of a few days for ethanol in sandy soil/groundwater microcosms.

Atmospheric Fate: Ethanol is expected to exist solely as a vapour in the ambient atmosphere. Vapour-phase ethanol is degraded in the atmosphere by reaction with photochemicallyproduced hydroxyl radicals; the half-life for this reaction in air is estimated to be 5 days. Ethanol readily degraded by reaction with photochemically produced hydroxy radicals; release into air will result in photodegradation and wet deposition.

Aquatic Fate: When released into water ethanol readily evaporates and is biodegradable. Ethanol is not expected to adsorb to suspended solids and sediment. Volatilization from water surfaces is expected and volatilization half-lives for a model river and model lake are 3 and 39 days, respectively. Bioconcentration in aquatic organisms is considered to be low. Hydrolysis and photolysis in sunlit surface waters is not expected to be an important environmental fate process for ethanol and is unlikely to be persistent in aquatic environments. DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
ethanol	LOW (LogKOW = -0.31)

Mobility in soil

Ingredient	Mobility
ethanol	HIGH (KOC = 1)

(SECTION 13) DISPOSAL CONSIDERATIONS

Waste treatment methods

- Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- ▶ Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

Product / Packaging disposal

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 21 OF 24

- ▶ Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
- ▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 TRANSPORT INFORMATION

	010110	TIVALITATION	THE ORIGINATION
Labels Required			
	3		
Marine Pollutant	NO		
HAZCHEM	•2Y		
Land transport (ADG)			
14.1. UN number or ID number	1170		
14.2. UN proper shipping name	ETHANOL (ETHYL ALCOHOL) or	ETHANOL SOLUTION (ETH	YL ALCOHOL SOLUTION)
14.3. Transport hazard	Class 3		
class(es)	Subsidiary Hazard Not Appli	cable	
14.4. Packing group	III		
14.5. Environmental hazard	Not Applicable		
14.6. Special precautions for	Special provisions 144 223		
user	Limited quantity 5 L	_	
Air transport (ICAO-IATA / DGI	3)		
14.1. UN number	1170		
14.2. UN proper shipping name	Ethanol or Ethanol. solution		
	ICAO/IATA Class	3	
14.3. Transport hazard	ICAO / IATA Subsidiary Hazard	Not Applicable	
class(es)	ERG Code	3L	
14.4. Packing group	III		
14.5. Environmental hazard	Not Applicable		
	Special provisions		A3 A58 A180
	Cargo Only Packing Instructions		366
	Cargo Only Maximum Qty / Pack		220 L
14.6. Special precautions for user	Passenger and Cargo Packing Instructions		355
4001	Passenger and Cargo Maximum	Qty / Pack	60 L
	Passenger and Cargo Limited Q	uantity Packing Instructions	Y344
	Passenger and Cargo Limited M	aximum Qty / Pack	10 L

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 22 OF 24

Sea transport (IMDG-Code / GGVSee)				
14.1. UN number	1170	1170		
14.2. UN proper shipping name	ETHANOL (ETHYL ALCO	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)		
14.3. Transport hazard class(es)	IMDG Class IMDG Subsidiary Hazar	IMDG Class 3 IMDG Subsidiary Hazard Not Applicable		
14.4. Packing group	III			
14.5 Environmental hazard	Not Applicable	Not Applicable		
14.6. Special precautions for user	EMS Number F-E, S-D Special provisions 144 223 Limited Quantities 5 L			

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
benzoin resinoid absolute Sumatra	Not Available
Styrax	Not Available
aloes	Not Available
ethanol	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
benzoin resinoid absolute Sumatra	Not Available
Styrax	Not Available
aloes	Not Available
Product name	Ship Type
ethanol	Not Available

(SECTION 15)

REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

benzoin resinoid absolute Sumatra is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

Styrax is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

aloes is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

ethanol is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

Australian Inventory of Industrial Chemicals (AIIC)

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au WEBSITE: www.livingstone.com.au PHONE: 1300 548 289 FAX: 1300 780 008



01/07/2025 Issue Date:

Last Revision Date: N/A Superseded Date: **Version Number:**

SAFETY DATA SHEET

Product Code: BEN537004 **PAGE 23 OF 24**

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (benzoin resinoid absolute Sumatra; Styrax; aloes; ethanol)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (benzoin resinoid absolute Sumatra; Styrax; aloes)
Korea - KECI	No (Styrax; aloes)
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	No (aloes)
Taiwan - TCSI	Yes
Mexico - INSQ	No (benzoin resinoid absolute Sumatra; Styrax)
Vietnam - NCI	Yes
Russia - FBEPH	No (benzoin resinoid absolute Sumatra; Styrax; aloes)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

(SECTION 16)

OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riordan Street ABN 66 052 001 144 Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE:** www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 01/07/2025

Last Revision Date: N/A Superseded Date: N/A Version Number: 01

SAFETY DATA SHEET

Product Code: BEN537004

PAGE 24 OF 24

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

END OF SDS