Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riodan Street Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE**: www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 04/11/2020 Last Revision Date: 10/08/2023 Superseded Date: 28/09/2021

Version Number: 03

SAFETY DATA SHEET

Product Code: LIVSAN1000N2

PAGE 1 OF 7

SECTION 1 PRODUCT IDENTIFICATION

Product Name Livingstone Antibacterial Hand and All-Purpose Sanitising Gel

Chemical Name Hand Sanitiser

SECTION 2 HAZARD IDENTIFICATION

GHS Classification Flammable liquids 2

Skin corrosion/irritation 2

Serious eye damage/eye irritation 2A

Gi4S Pictograms



Signal words Danger -

Hazard statements H225: Highly flammable liquid and vapour

H315: Causes skin irritation

H319: Causes serious eye Irritation

Precautionary Statement P210 Keep away from heat/sparks/open flames/hot surfaces.-No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P264: Wash hands thoroughly after handling.-

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement

Response

P302+P352: IF ON SKIN: Wash with plenty of water.

P303+p361+P353: IF ON SKIN (or hair): Take off imrriediately all contaminated clothing. Rinse skin with

water/shower. P305+P351+p338: IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. P321: Specific treatment (see the supplemental first aid instruction).

P332+P313: If skin irritation occurs: Get medical advice/attention. P337+p313: If eye irritation persists: Get medical advice/attention. P362+p364: Take off immediately contaminated clothing and

wash it before reuse.

P370+P378: In case of fire: Use extinguisher to extinguish.

Precautionary Statement

Storage

P403+P235: Store in a well-ventilated place. Keep cool.

Precautionary Statement P501: Dispose of contents/container in according with local regulation.

Other hazards which do not result in classification

Not available.

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riodan Street Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE**: www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



 Issue Date:
 04/11/2020

 Last Revision Date:
 10/08/2023

 Superseded Date:
 28/09/2021

SAFETY DATA SHEET

Product Code: LIVSAN1000N2

0.3

PAGE 2 OF 7

SECTION 3

COMPOSITION/INFORMATION ON INGREDIENTS

Substances Mixtures Component Information

Version Number:

Component	CAS number	EINECS number	Mass(%)
ALCOHOL	64-17-5	200-578-6	75.0%wt
WATER	7732-18-5	231-791-2	24.3 % wt
CARBOMER	9062-04-8		0.4%wt
TRIETHANOLAMINE	102-71-6	203-049-8	0.3%wt

Note: 1. Unless a component presents a severe hazard, it does not need to be considered in the SDS if the concentration is less than i %

SECTION 4 FIRST AID MEASURES

NOTE TO PHYSICIAN In case of shortness of breath, give oxygen. Keep virtim warm.

Keep victim under observation. Symptoms may be delayed.

After inhalation Move to fresh air. Oxygen or artificial respiration if needed. Get

immediate medical attention.

After skin contact Immediately flush skin with plenty of water. Remove and Isolate contaminated clothing and shoes.--If

irritation persists, get medical attention immediately. For minor skin contact, avoid spreading material

on unafferted skin. Wash clothing separately before reuse.

After eye contact Immediately flush eyes with plenty of water for at least 15 minutes-. Assure adequate flushing of the

eyes by separating the eyelids with fingers. Get medical attention immediately.

After ingestion Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward

to reduce risk of aspiration. Loosen tight clothing such as a collar, tie, belt or waistband.- Do not use mouth-to-mouth-_method if victim ingested the substance. Seek immediate medical attention.

Most important

symptoms/efferts, acute

and delayed

Causes skin irritation. Causes serious eye irritation.

CECTION E

FIRE FIGHTING MEASURES

Suitable extinguishing agents

Water spray, foam, CO21 dry chemical Suitable extinguishing powder, sandy soil. _

Special hazards caused by the material, its products of combustion or flue gases

Can be released in case of fire:

Carbon monoxide, carbon dioxide, nitrogen oxides.

Protective equipment for fire-fighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand

breathing apparatus protective clothing and face mask.

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riodan Street Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE**: www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 04/11/2020 Last Revision Date: 10/08/2023 Superseded Date: 28/09/2021

Version Number: 03

SAFETY DATA SHEET

Product Code: LIVSAN1000N2

PAGE 3 OF 7

SECTION 6

ACCIDENTAL RELEASE MEASURES

Person-related safety precautions

Ensure adequate ventilation. Remove all sources of ignition, Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Ventilate closed spaces before entering. Keep unnecessary personnel away.

Measures for environmental

protection
Measures for cleaning/collecting

Prevent further leakage or spillage if safe to do so. Do not allow material to be released to the

environment without proper governmental permits.

Contain spillage, and then collect with non-combustible absorbent material(e.g. sand, earth, diatomaceous earth, vermiculite) and place In suitable container. Clean contaminated surface thoroughly.

Can not be mixed with flammable and explosive goods, etc.. Prevent the sun-rain and heavy pressure.

Additional information See Section 7 for information on safe handling

See section 8 for information on personal protection equipment:

See Section 13 for information on disposal.

SECTION 7

HANDLING AND STORAGE

Handling

Information for safe

handling

Avoid breathing vapors, mist or gas, Keep out of reach of children. In case of insufficient ventilation, wear suitable respiratory equipment if Ingested.

Information about protection against explosions and fires

Don't put near the hot water or heat sink, stove, or other heat sources. Keep away from open fire or heat.

Storage Do

Requirements to be met by

Do not put it in more than 50 'C or damp place. Store in a cool, dry place below 50°C Put it away from the touch of kids. Keep container closed.

storerooms and containers

Information about storage in one

common storage facility

Further information about storage conditions

Store away from incompatible substances such as strong oxidizing agents, acidic materials. No data.

SECTION 8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Limit Values for Exposure

Component	CAS number	ACGIH TLV-TWA	ACGIH TLV-STEL	NIOSH PEL-TWA	NIOSH PEL-STEL		
ALCOHOL	64-17-5	N.E.	1,880 ACGIHmg/m ³	1,900mg/m ³	N.E.		
CARBOMER	9062-04-8	N.E.	N.E.	N.E.	N.E.		
TRIETHANOLAMINE	102~71-6	5 mg/m ³	N.E.	N.E.	N.E.		
Appropriate engineering Controls	Facilities storing or utilizing this material should be equipped, with an eyewash and a safety shower facility.						
General protective and hygienic measures	Do not get this material in contact with eyes. Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday						
Personal protective equipment	Dust masks, air apparatus, safety glasses, protective clothing, latex gloves.						
Breathing equipment	When workers are facing concentrations above the exposure limit they must use appropriate certifled respirators.						
Protection of hands	Wear appropriate chemical resistant gloves.						
Eye/Face protertion	Use safety glasses with side shields or safety goggles as mechanical barrier for prolonged exposure,						
Body protection	Full set of anti chemical reagent overalls, flame retardant antistatic protective clothing, choose body protection according to the amount and concentration of the dangerous substance at the work place.						

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riodan Street Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au WEBSITE: www.livingstone.com.au PHONE: 1300 548 289 FAX: 1300 780 008



Issue Date: 04/11/2020 Last Revision Date: 10/08/2023 Superseded Date: 28/09/2021

SAFETY DATA SHEET

Product Code: LIVSAN1000N2

PAGE 4 OF 7

(SECTION 9) PHYSICAL/CHEMICAL PROPERTIES

Appearance (physical state,

colour etc)

Colorless viscous liquid

Odour

Version Number:

Faint smell

рΗ

6.5~8.0 (Concentration: 10 %, Temperature:25°C) -

Melting point/freezing point

Boiling point and boiling

No data available

Flash point

21.0 °C (closed cup)

Evaporation rate

No data avallable

Flammability

Highly flammable

Upper/lower flammability or explosive limits

No data available

Vapour pressure Vapour density(air-l) No data available No data available

Density/Relative density

Solubility(water)

0.9 (25°C)

Soluble

Partition coefficient:

n-octanol/water

No data avallable

Auto-ignition temperature

No data avallable

No data avallable

Decomposition temperature

Viscosity

No data avallable

SECTION 10

STABILITY AND REACTIVITY

Chemical stability

Stable under normal temperature.

Possibility of hazardous

No polymerization.

reactions

Conditions to avoid (e.g. static discharge, shock or vibration)

Heat and flame and spark. The extreme temperatures and direct sunlight.

Incompatible materials

Avold contact with strong oxidizing agents, acidic materials.

Hazardous decomposition

May Include carbon monoxide, carbon dioxide, nitrogen oxides.

products

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riodan Street Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE**: www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 04/11/2020 Last Revision Date: 10/08/2023 Superseded Date: 28/09/2021

SAFETY DATA SHEET

Product Code: LIVSAN1000N2

PAGE 5 OF 7

SECTION 11 TOXICOLOGICAL INFORMATION

This product is a preparation for which no toxicological data exists. When available, toxicological data for the product's hazardous ingredients are provided below. Routes of Entry: Dermal contact, eye contact, inhalation, ingestion.

Acute Toxicity

Version Number:

ALCOHOL (CAS 64-17-5) LD50 (Oral,rat) 7,060 mg/kg

LC50 (Inhalation,rat) 124.7 mg/l (4 h)

LD50 (Dermal, rabbit) N/A

CARBOMER (CAS LD50-. (oral,rat)= >1,000 mg/kg

9062-04-8) LC50 (Inhalation,rati N/A

LD50 (Dermal,rabbit) N/A

TRIÉTHANOLAMINE (CAS LD50 - (Oral, gutnea pig)_2,200 mg/kg

LC50 (Inhalation,rat) N/A

LD50 _-(Dermal,rabbit) :=>22,500 mg/kg

Skin corrosion/Irritation Causes skin irritation.

Serious damage/irritation eye-_ Causes-_severe eye irritation, conjunctiva redness and swelling.

Respiratory or sensitization No data available for this chemical. Germ cell mutagenitcity No data available for this chemical No data available for this chemical. Carcinogenicity No data available for this chemical. Reproductive toxicity STOT~single exposure No data available for this chemical. STOT-repeated exposure No data available for this chemical. Aspiration hazard No data available for this chemical. **Chronic Effects** No data available for this chemical. **Further Information** No data available for this chemical.

(SECTION 12) ECOLOGICAL INFORMATION

Ecotoxicity

ALCOHOL (CAS 64-17-5

Test & Species

96 Hr LC50 fish: 11,000 mg/l 24 Hr EC50 Daphnia: > 10,000 mg/l

72 Hr EC50 Algae: N/A

TRIETHANOLAMINE (CAS 102-71-6)

Test & Species

96 Hr LC50 fish: 450-1,000 mg/l 48 Hr EC50 Daphnia: 609.98 mg/l

72 Hr EC50 Algae: N/A

Persistence and degradability Not available

Bioaccumulative potential No bioaccumulative.

Mobility in soilNot availableAdditional InformationNot available

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riodan Street Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au WEBSITE: www.livingstone.com.au PHONE: 1300 548 289 FAX: 1300 780 008



Issue Date: 04/11/2020 Last Revision Date: 10/08/2023 Superseded Date: 28/09/2021

Version Number:

SAFETY DATA SHEET

Product Code: LIVSAN1000N2

PAGE 6 OF 7

SECTION 13 DISPOSAL CONSIDERATIONS

WASTE DISPOSAL INSTRUCTIONS

Contact a licensed professional waste disposal service to dispose of this material. Dispose of in accordance with local environmental regulations or local authority requirements

(SECTION 14) TRANSPORT INFORMATION

The Recommendation of Transport of Dangerous Goods(TDG)

UN Number UN 1170

Proper Shipping Name ETHANOL SOLUTION

Class/Division Class 3 Flammable Liquids

Package Group PGII Subsidiary risk None

labelling program



Maritime transport Being same with TDG/No

IMDG/ Marine pollutant

(Yes/No)

Air transport ICAO-TI

and IATA~DGR

Being same with TDG

REGULATORY INFORMATION

European/International

Regulations

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

EINECS Status: ALCOHOL (CAS 64-17-5), WATER (CAS 7732-18-5) and TRIETHANOLAMINE (CAS 102-71-6) are included in

EINECS inventory,

EPA TSCA Status: ALCOHOL (CAS 64-17-5), WATER (CAS 7732-18-5) and TRIETHANOLAMINE (CAS 102-71-6) are included in

TSCA inventory.

Canadian ALCOHOL (CAS 64-17-5), WATER (CAS 7732-18-5), CARBOMER DsL(Domestic (CAS 9062-04-8) and TRIETHANOLAMINE (CAS 102-71-6) are

Substances List): included in DSL

HMIs(Hazardous Health: 2 **Material Identification** Flammability: 3 Personal protection: E System Ratings):

(4. Severe Hazard. 3. Serious Hazard; 2. Moderate Hazard; 1. Slight Hazard; 0. Mlnimal Hazard)

WHMIS(Canadian B2,D2B (ALCOHOL).

Workplace Hazardous **Material Identification** System Ratings): GB 12268-2012 List of

This produtt is a dangerous goods on the GB 12268=2012 llst of dangerous goods.

dangerous goods

Branches in Sydney, Melbourne, Brisbane and Perth HEAD OFFICE: Suite 1, Level 9, Building 3, 189 O'Riodan Street Mascot NSW 2020 AUSTRALIA

EMAIL: sales@livingstone.com.au **WEBSITE**: www.livingstone.com.au

PHONE: 1300 548 289 **FAX**: 1300 780 008



Issue Date: 04/11/2020 Last Revision Date: 10/08/2023 Superseded Date: 28/09/2021

Version Number:

28/09/2021

SAFETY DATA SHEET

Product Code: LIVSAN1000N2

PAGE 7 OF 7

(SECTION 16)

OTHER INFORMATION

This Material Safety Data Sheet was based on the "Globally Harmonized System of Classification and Labelling of Chemicals" Recommendations on the TRANSPORT OF DANGEROUS GOODS - Model Regulations , INTERNATIONAL-MARITIME DANGEROUS GOODS CODE , International Air Transport Association Dangerous Goods Regulations" the National __ Standards and other related dangerous chemicals management. laws, regulations and standards, which are periodically updated and changed. To make dangerous goods / hazardous chemicals comply with the relevant requirements of the latest

management, regularly update is recommended. This Material Safety Data Sheet has been compiled in both English and Chinese. For any discrepancies, the Chinese version shall prevail.

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulations Concerning the International Transport of

Dangerous Goods by Rail IMDG: International Maritime Code for Dangerous Goods

IATA~DGR: Dangerous Goods Regulations by the "International

Air Transport Association" (IATA)

ICAO-TI: Technical Instructions by the "International Civil

Aviation Organization. (ICAO)

EINECS: European Inventory of Existing Commercial Chemical

Substances

CAS: Chemical Abstrarts Service LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Reason for Revision:

To bring to date

END OF SDS